### TOWN OF MACKLIN

Revised October 31, 2014

2.0 meters (6.5 feet)

## **QUICK REFERENCE – RESIDENTIAL DETACHED GARAGE**

<u>A building permit is only valid for 180 days</u>, if the work has not started prior to this period; a new permit must be obtained, unless prior written approval has been granted. All contractors are required to be licensed with the Town and should be listed on the permit. It is the responsibility of the owner and contractor of this project to ensure that all requirements of the National Building Code and the Uniform Building and Accessibility Standards Act are adhered to and followed.

#### **PLOT PLAN:**

- Submit in ink a plot plan drawn to scale on an 8 ½" x 11" paper indicating the direction (north).
- Show the lot size, locations of all existing and proposed buildings and all setbacks.
- Date and sign the plot plan include civic address and legal description.
- Submit a copy of a surveyor's certificate if available.

#### **PROPERTY PIN LOCATION:**

- It is the property owner's responsibility to find the property pins.
- The Town of Macklin maintenance employees <u>may</u> find property pins but this will be done once and if time is available. This shall be at the discretion of the Town Foreman.

#### **PROPERTY SET BACKS:**

The minimum set back requirement for the R-1 Residential District. All measurements shall be from the property line.

#### **Single Detached Dwelling**

# <u>Accessory Buildings</u> 6 meters (20 feet) Side Yard Doors To Lane

Rear Yard 7.5 meters (25 feet) Side Yard Doors To Street 3.6 meters (12.0 feet) Side Yard No Doors 0.8 meters (2.6 feet) Side Yard (corner lot 2.5 meters 8.2 feet) Maximum Wall Height 4.0 meters (13.0 feet)

Lot Coverage to a maximum of 40 percent or 50% on a corner lot

#### **SERVICES:**

Front Yard

- The homeowner is responsible for the sewer and water installation from the main service line.
- If pavement and curb have to be destroyed in order for the connection to be made, the homeowner will be invoiced for the cost.
- A utility deposit is required to hook up water. This deposit is refunded by either applying to the final bill, or refunding back to the applicant if account is paid in full.

#### **MOVED-IN BUILDINGS:**

• All garages being moved into the Town of Macklin require a minimum of one (1) interior and four (4) exterior pictures (of all sides)

#### **IMPORTANT NOTES**

- Only one detached garage, not to exceed 83.6 square meters (900 sq.ft.), is allowed in any residential district.
- Accessory buildings are not to be located in any front yard.
- Accessory buildings are not to exceed the height of the principal building to a maximum of 5.0 meters height.
- Accessory buildings shall be located at least 1.2 meters (4 feet) from the principal building.
- All listed set backs are minimum requirements as per Zoning Bylaw



#### PERMITS & INSPECTIONS

1 lovdminster

Fort McMurray

Red Deer

Lethbridge

Bay 1, 2914 - 50 Avenue 3, 6264 - 67A Street

422 North Mayor Magrath Drive

165, 101 Signal Road

T9V 3B4

T4P 3E8

T9H 4N6

T1H 6H7

Ph; 780-870-9020

Ph: 403-358-5545

Ph: 780-715-7726

Ph: 403-320-0734

Fax: 780-870-9036

Fax: 403-358-5085

Fax: 780-715-7731

Fax: 403-320-9969

Toll Free Ph: 1-888-358-5545

Toll Free Ph: 1-877-715-7726

Toll Free Ph: 1-877-320-0734


Toll Free Fax: 1-866-358-5085

Toli Free Fax: 1-877-715-7731

#### **ACCESSORY BUILDING**

PERMIT NO.:	
OWNERS NAME:	
PROJECT LOCATION:	

#### To be completed and attached to the Building Permit Application Form



Please check off garage construction details as listed below. Please Note: **Roofing Material** Wall Sheathing Windows cannot be placed in a wall that is closer than 4 feet to ☐ Asphalt Shingles ☐ 3/8" OSB neighbour's property. ☐ Cedar, Pine Shakes/Shingles 3/8" plywood Metal Roofing 1/2" plywood If the roof framing members transfer Other Specify: \_ ☐ 1/2" OSB roof loading to the overhead garage door beam please specify the size of ☐ Other Specify: the garage door beam. Roof Sheathing **Wall Framing** ☐ Min. 3/8" OSB or plywood ☐ 2 x 4 @ 16" o.c. Large opening size (doors over 20 feet wide) garage door beams NOTE: OSB or plywood less than ½" requires H clips and \( \square 2 \times 4 @ 24" \) o.c. without roof loading must be minimum bridge blocking \*Max wall height 9.8 ft (3.0 m) size 2 - 2 x 12 c/w a minimum of 3" ☐ ½" OSB or plywood 2 x 6 @ 16"/24" o.c. bearing. ☐ Other Specify: \_\_ ☐ Insulated walls & ceiling Maximum size of detached garage on Roof Framing **Garage Door Beam** a slab thickening foundation is 728 ☐ Pre-manufactured Engineered Truss Lenath: sq. ft. with truss span not exceeding ☐ Stick Build Rafters (provide details) Depth: # of Plys 28 feet. Oversized garage will require review and approval by a Safety ☐ Built Up Engineered Codes Officer. **Exterior Finish** Garage Door Size: Vinyl Siding **Direction of Trusses** Walls to be secured to slab with anchor bolts at 8' on center Stucco □ Trusses parallel to overhead door maximum. Metal Siding Other Specify: ☐ Trusses perpendicular to overhead Cannot build over an underground door opening gas line. **Foundation** 4" Slab with Thickened Edges Other Foundation (details, engineering) ☐ Strip footing & 4' frost wall **Interior Development** NOTE: A separate permit is required for each of these items (if applicable) ☐ Electrical ☐ Gas ☐ Plumbing ☐ Other (specify): \_ Calgary 25, 2015 - 32 Avenue NE T2E 6Z3 Ph: 403-717-2344 Fax: 403-717-2340 Toll Free Ph: 1-888-717-2344 Toll Free Fax: 1-888-717-2340 Edmonton 14613 - 134 Avenue T5L 4S9 Ph: 780-489-4777 Fax: 780-489-4711 Toll Free Ph: 1-866-999-4777 Toll Free Fax: 1-866-999-4711 Grande Prairie 10525 - 100 Avenue **T8V 0V8** Ph: 780-882-8777 Fax: 780-882-7677 Toll Free Ph: 1-877-882-8777 Toll Free Fax: 1-877-882-8775